



Visi Coolers



- * Fan assisted cooling
- * Front hot air blowing to prevent condensation on glass, excellent for display
- * Inside fan for ventilation, achieving even temperature
- * Replaceable gasket for hygiene
- * 1 vertical inside light, full illumination for each layer
- * Adjustable shelves for merchandising
- * Mechanical controller, adjustable
- * Full length extruded handle, elegant
- * Double glazing, self-closing glass door, one layer tempered for safety
- * Painted aluminum interior
- * Inside drain hole, self-evaporation water tray, convenient
- * 4 strong casters, front 2 with brake, easy move & stop
- * With lock and key



- | | | |
|------------------------------------|-----------------------------|------------------------------|
| adjustable shelves | tempered glass door | Options: |
| front blower to avoid condensation | self-evaporation water tray | - sticker |
| 2 inner vertical light | lock fitted | - graved logos on glass door |
| digital control | | - without light box |

Model	Dimension (mm)	Capacity	Temperature	Power Consumption	Power Supply	No. of Door	No. of Shelves	Weight (kg)
#CS-200	540×510×1580	200	0~10 °C	1.4KW/24h	220v/50Hz	1	3	60/52
#CS-400	610×620×1940	400	0~10 °C	2.3KW/24h	220v/50Hz	1	4	90/83
CSD-600	945×640×1985	600	0~10 °C	3.5KW.h/24h	220v/50Hz	2	8	140/122
CSD-1000	1130×725×2025	1000	0~10 °C	5.6KW.h/24h	220v/50Hz	2	8	175/155



Deep Freezer



- * Embossed aluminum interior
- * Elegant extruded handle
- * Mechanical controller, adjustable
- * Inside stepped bottom
- * 4 strong casters, front 2 with brake, easy move & stop
- * Unique drainage design for easy cleaning
- * Solid foam door or sliding heat-reflective tempered glass door



- Metal Basket
- Inner Light
- Handle
- Foaming Door
- Static Cooling System
- Temp.Control
- Inside Body
- Caster
- Lock & Key

Model	Door Type	Temp.Range	Volume	Dimensions(W*D*H)		Weight(kgs)	
				Product	Package	Net	Gross
FC-100	Foaming Door	≤-18℃	100L	610x550x850	630x580x890	30	33
FC-200	Foaming Door	≤-18℃	200L	860x550x850	885x580x890	36	38
FC-300	Foaming Door	≤-18℃	280L	1080x670x850	1130x690x890	40	44
FC-400	Foaming Door	≤-18℃	400L	1430x750x850	1480x775x890	55	62
FC-500	Foaming Door	≤-18℃	500L	1650x750x850	1700x775x890	63	69
FC-650	Foaming Door	≤-18℃	650L	1860x750x850	1910x775x890	66	72



Glass Door Chest Freezer



- * Flat glass door chest freezer
- * With lock and key
- * Embossed aluminum interior
- * Elegant extruded handle
- * Mechanical controller, adjustable
- * Inside stepped bottom
- * 4 strong casters, front 2 with brake, easy move & stop
- * Unique drainage design for easy cleaning
- * Heat reflective tempered glass door



Model	Door Type	Temp.Range	Volume	Dimensions(W*D*H)		Weight(kgs)	
				Product	Package	Net	Gross
FCG-250C	Curved Glass Door	≤-18 °C	250L	1095x600x830	1155x655x890	51	55
FCG-350C	Curved Glass Door	≤-18 °C	350L	1295x600x830	1355x655x890	60	66

Model	Door Type	Temp.Range	Volume	Dimensions(W*D*H)		Weight(kgs)	
				Product	Package	Net	Gross
FCG-100	Flat Glass Door	≤-18 °C	100L	610x520x810	625x580x855	31	35
FCG-200	Flat Glass Door	≤-18 °C	200L	870x520x810	885x580x855	35	40
FCG-320	Flat Glass Door	≤-18 °C	320L	1270x590x810	1315x685x855	48	52
FCG-400	Flat Glass Door	≤-18 °C	400L	1440x680x810	1485x775x855	54	58
FCG-500	Flat Glass Door	≤-18 °C	500L	1650x680x810	1695x775x855	63	67

- Metal Basket
- Caster
- Glass Door
- Handle
- Inside Body
- Temp.Control
- Lock & Key
- Static Cooling System





Wine Chiller



- * Double temperature cabinets
- * Dynamic cooling
- * Inside fan for ventilation, achieving even temperature
- * #304 stainless steel glass door, one layer tempered for safety, anti-UV
- * Elegant blue LED inside light for illumination
- * Ball bearing sliding shelves
- * Digital controller with blue LED display & defrost timer
- * #304 stainless steel handle
- * Aluminum buttons



adjustable wood shelves

self-evaporation water tray

tempered glass door

digital control

inner LED light

lock fitted

Model	Dimension (mm)	Capacity	Bottle Capacity	Temperature	Power Consumption	Power Supply	No. of Door	No. of Shelves	Weight (kg)
WD-38	435×580×1020	125	35-50	3-22 °C	0.74KW.h/24h	220v/50Hz	1	7	46/43
WD-66	635×580×1020	190	66-80	3-22 °C	1KW.h/24h	220v/50Hz	1	7	56/53.5
WD-180	650×680×1840	480	181-210	3-22 °C	1.4KW.h/24h	220v/50Hz	1	8	117/112





Back Bar Bottle Counter



RGB LED Lights Optional

- * Inside fan for ventilation, achieving even temperature
- * Inside light for illumination
- * Replaceable gasket for hygiene
- * Adjustable chrome shelves for merchandising
- * Carel digital controller with LED display & defrost timer
- * Embossed aluminum interior
- * Textured exterior body, avoids scratch
- * Elegant extruded handle
- * Double glazing, self-closing glass door, one layer tempered for safety
- * Inside drain hole, self-evaporation water tray, convenient
- * Available at various heights 90cm, 87cm and 84cm
- * With lock and key
- * 2 adjustable legs



adjustable wood shelves

self-evaporation water tray

tempered glass door

digital control

inner LED light

lock fitted

Hinge Door Range

Model	Cooling System	Temp. Range	Volume	Product	Packages	Net	Gross
BB-1	Single Door	0~210 °C	130L	600x520x900	650x570x980	46	50
BB-2	Double Door	0~10 °C	210L	900-520x900	955x570x980	62	69
BB-3	Triple Door	0~10 °C	320L	1350x520x900	1400x570x980	82	90

Sliding Door Range

BB-2S	Double Door	0~210 °C	210L	900x520x900	955x570x980	62	69
BB-3S	Triple Door	0~10 °C	320L	1350x520x900	955x570x980	82	90



Technical Specification

	Unit	CFMD	C-10/10	C-15/20	C-20/40	C-40/80	C-60/120	C150/150	C150/400	C150R
Model			C-50	C-75	C-100	C-200	C-300	C-800	C-800	800
Cooling Capacity *	Lt/hr.	3	10	15	20	40	60	150	150	150
At 10°C	Lt/hr.	5	15	25	30	65	100	245	245	245
Glassess 200ml./hr. at rated Cond.**	No.	15	50	75	100	200	300	800	800	800
Storage Capacity	Ltr.	3	10	20	40	80	120	150	400	
Material of Tank	SS	SS	SS	SS	SS	SS	SS	SS	SS	Brass
Dip Tray	SS	SS	SS	SS	SS	SS	SS	SS	SS	NA
Faucets/Push Cocks	No.	2	1	1	2	2	2	2	3	2
Compressor/Refrigerant	Recip/134A	Recip/134A	Recip/134A	Recip/134A	Recip/134A	Recip/R-22	Recip/R-22	Recip/R-22	Recip/R-22	Recip/R-22
Voltage Range										
Power Input (Max.)	Watt	90/500	125	125	250	510	710	1500	1500	1500
Rated current Amp.		0.6	1.2	1.5	1.8	2.5	3.6	2	2	7.2
Dimensions										
Height	mm	335	600	1200	1200	1200	1330	1500	1500	910
Width	mm	320	410	410	410	635	635	635	635	640
Depth	mm	330	410	410	410	460	562	562	686	550